

Tango Classic

2020

WOOD
product
data
sheet



pattern: 1 strip

Classics never go out of fashion. Modern at all times, attractive to different generations. Creating classics asks for special kind of innovation, because in order to become timeless, something must be new at first. With the idea of designing beauty and quality that passes the test of time and makes home warm and comfortable, we designed Classic. Tango Classic.

board size: 1200 x 164 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface oil	gloss level	brushed	heat treatment	bevel	dop number
Essential Pure / White	550182001	ASH ALABASTER BR	Ash	Nature	No	No	PHO	5-8	Yes	No	4 side	DoP 2702-0012-2016-12
Essential Pure / Antique White/Grey	550182002	OAK BRIGHT BR 1200	Oak	UNI Nature + UNI Rustic	No	No	PHO	5-8	Yes	No	4 side	DoP 2702-0012-2016-12
Essential Classic / Beige	550182003	OAK SEPIA BR 1200	Oak	UNI Nature	No	No	PHO	5-8	Yes	No	4 side	DoP 2702-0012-2016-12
Essential Brown / Mocha	550182005	OAK COPPER BR 1200	Oak	UNI Nature	No	No	PHO	5-8	Yes	No	4 side	DoP 2702-0012-2016-12
Essential Brown / Mocha	550182006	OAK SIENNA BR 1200	Oak	Uni Nature + Uni Rustic	No	No	PHO	5-8	Yes	No	4 side	DoP 2702-0012-2016-12
Essential Classic / Beige	550182007	OAK ALMOND BR 1200	Oak	UNI Robust + UNI Rustic	No	No	PHO	5-8	Yes	No	4 side	DoP 2702-0012-2016-12
Essential Classic / Nature	550182008	OAK COTTAGE BR 1200	Oak	UNI Rustic	No	No	PHO	5-8	Yes	No	4side	DoP 2702-0012-2016-12
Essential Brown / Mocha	550182027	OAK GINGER BR 1200	Oak	UNI Rustic	No	No	PHO	5-8	Yes	No	4side	DoP 2702-0012-2016-12

PHO - Protoco Hardwax Oil

installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-50%.
- Room temperature: 18-24°C.



T-LOCK

Tarkett lock, glue-free locking system

AQUA GUARD

Extended liquid resistance at the short side of boards connection

HEALTHY FLOORS

Lacquer properties prevent bacteria reproduction

ENVIRONMENTAL COMMITMENT

Environmental responsibility throughout all processes (C2C, FSC, ISO14001)

WARRANTY

30 years residential warranty

maintenance

— The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1— WET MOPPING OR VACCUMING: Wet mopping with almost dry cloth. Use protective pads when moving furniture
- 2— DRY CLEANING: Dry mopping & vaccum cleaning
- 3— REGULAR CLEANING: Osmo Wash and Care
- 4— OCCASIONAL INTENSIVE CLEANING: Osmo Liquid Wax Cleaner
- 5— PROTECTION PRESERVATION AND RENEWAL: Osmo Polyx®-Oil



underfloor heating

— Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.

*Not suitable for the wood species beech and maple

technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m ³	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,11 W/m K	
H – Biological durability	Class 1	

size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	164
Length (mm)	1200/1000
Wear layer thickness (mm)	~2,8
Boards/pack	6
m ² /pack	1,182
m ² /pallet	70,92
Weight/m ² (kg)	~6,70

design overview

