



DoP - Declaration of Performance

0120-033DoP-2013-04

DECLARATION OF PERFORMANCE

N° 0120-033DoP-2013-04

Regulation (UE) n°305/2011

1. Unique identification code of the product-type:
[Tapiflex evolution spice&candy](#)
2. Serial number allowing identification of the construction product:
[3626 / 25006 / 25501,](#)
3. Intended use(s):
[Polyvinyl chloride floor covering for indoor use in compliance with the harmonized standard EN 14041:2004.](#)
4. Name and contact address of the manufacturer:
[2 Avenue François SOMMER F-08203 Sedan Cedex, France](#)
5. System(s) of assessment and verification of constancy of performance:
System 3: Reaction to fire
[Reaction to fire: LNE, notified body N° 0071, carried out testing and provided test report N° N070367-DE/8 according to system 3.](#)
System 4: Other performance
6. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
A – Reaction to fire	Bfl s1	glued on an A1fl and / or A2fl substrate.	EN 14041:2004
	NPD	loose-laid on an A1fl and/or A2fl substrate.	
	Cfl S1	glued on a wooden sub-floor.	
	NPD	loose-laid on a wooden sub-floor.	
B – Content of pentachlorophenol	<5ppm		
C – Formaldehyde emission	E1		
D – Water-tightness	classification of EN 13553		
E – Slipperiness	DS		
F – Antistatic performance	< 2kV		
G – Electrical resistance	≥10E9Ω		
H – Thermal resistance	0.04 m² K/W		

The performance of the product identified above is in conformity with the declared performances. According to the regulation (EU) n°305 / 2011, the present declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Edgard Houssine , Plant Manager
FR-Sedan, 4/1/2013



Signature




DoP - Declaration of Performance

0120-035DoP-2013-04

DECLARATION OF PERFORMANCE

N° 0120-035DoP-2013-04

Regulation (UE) n°305/2011

1. Unique identification code of the product-type:
[Tapiflex evolution salt&pepper](#)
2. Serial number allowing identification of the construction product:
[4549 / 25502,](#)
3. Intended use(s):
[Polyvinyl chloride floor covering for indoor use in compliance with the harmonized standard EN 14041:2004.](#)
4. Name and contact address of the manufacturer:
[2 Avenue François SOMMER F-08203 Sedan Cedex, France](#)
5. System(s) of assessment and verification of constancy of performance:
System 3: [Reaction to fire](#)
[Reaction to fire: LNE, notified body N° 0071, carried out testing and provided test report N° N070367-DE/8 according to system 3.](#)
System 4: [Other performance](#)
6. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
A – Reaction to fire	Bfl s1	glued on an A1fl and / or A2fl substrate.	EN 14041:2004
	NPD	loose-laid on an A1fl and/or A2fl substrate.	
	Cfl S1	glued on a wooden sub-floor.	
	NPD	loose-laid on a wooden sub-floor.	
B – Content of pentachlorophenol	<5ppm		
C – Formaldehyde emission	E1		
D – Water-tightness	classification of EN 13553		
E – Slipperiness	DS		
F – Antistatic performance	< 2kV		
G – Electrical resistance	≥10E9Ω		
H – Thermal resistance	0.04 m² K/W		

The performance of the product identified above is in conformity with the declared performances. According to the regulation (EU) n°305 / 2011, the present declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Edgard Houssine , Plant Manager
FR-Sedan, 4/1/2013



Signature




DoP - Declaration of Performance

0120-034DoP-2013-04

DECLARATION OF PERFORMANCE

N° 0120-034DoP-2013-04

Regulation (UE) n°305/2011

1. Unique identification code of the product-type:
[Tapiflex evolution sand](#)
2. Serial number allowing identification of the construction product:
[4547 / 25500,](#)
3. Intended use(s):
[Polyvinyl chloride floor covering for indoor use in compliance with the harmonized standard EN 14041:2004.](#)
4. Name and contact address of the manufacturer:
[2 Avenue François SOMMER F-08203 Sedan Cedex, France](#)
5. System(s) of assessment and verification of constancy of performance:
System 3: [Reaction to fire](#)
[Reaction to fire: LNE, notified body N° 0071, carried out testing and provided test report N° N070367-DE/8 according to system 3.](#)
System 4: [Other performance](#)
6. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
A – Reaction to fire	Bfl s1	glued on an A1fl and / or A2fl substrate.	EN 14041:2004
	NPD	loose-laid on an A1fl and/or A2fl substrate.	
	Cfl S1	glued on a wooden sub-floor.	
	NPD	loose-laid on a wooden sub-floor.	
B – Content of pentachlorophenol	<5ppm		
C – Formaldehyde emission	E1		
D – Water-tightness	classification of EN 13553		
E – Slipperiness	DS		
F – Antistatic performance	< 2kV		
G – Electrical resistance	≥10E9Ω		
H – Thermal resistance	0.04 m² K/W		

The performance of the product identified above is in conformity with the declared performances. According to the regulation (EU) n°305 / 2011, the present declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Edgard Houssine , Plant Manager
FR-Sedan, 4/1/2013


Signature




DoP - Declaration of Performance

0120-032DoP-2013-04

DECLARATION OF PERFORMANCE

N° 0120-032DoP-2013-04

Regulation (UE) n°305/2011

1. Unique identification code of the product-type:
[Tapiflex evolution vision](#)
2. Serial number allowing identification of the construction product:
[3628 / 3695 / 3864 / 4530 / 4531 / 4551 / 4695 / 25007 / 25503 / 25506](#),
3. Intended use(s):
[Polyvinyl chloride floor covering for indoor use in compliance with the harmonized standard EN 14041:2004.](#)
4. Name and contact address of the manufacturer:
[2 Avenue François SOMMER F-08203 Sedan Cedex, France](#)
5. System(s) of assessment and verification of constancy of performance:
System 3: Reaction to fire
[Reaction to fire: LNE, notified body N° 0071, carried out testing and provided test report N° N070367-DE/8 according to system 3.](#)
System 4: Other performance
6. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
A – Reaction to fire	Bfl s1	glued on an A1fl and / or A2fl substrate.	EN 14041:2004
	NPD	loose-laid on an A1fl and/or A2fl substrate.	
	Cfl S1	glued on a wooden sub-floor.	
	NPD	loose-laid on a wooden sub-floor.	
B – Content of pentachlorophenol	<5ppm		
C – Formaldehyde emission	E1		
D – Water-tightness	classification of EN 13553		
E – Slipperiness	DS		
F – Antistatic performance	< 2kV		
G – Electrical resistance	≥10E9Ω		
H – Thermal resistance	0.04 m² K/W		

The performance of the product identified above is in conformity with the declared performances. According to the regulation (EU) n°305 / 2011, the present declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Edgard Houssine , Plant Manager
FR-Sedan, 4/1/2013



Signature




DoP - Declaration of Performance

0120-031DoP-2013-04

DECLARATION OF PERFORMANCE

N° 0120-031DoP-2013-04

Regulation (UE) n°305/2011

1. Unique identification code of the product-type:
[Tapiflex evolution uni](#)
2. Serial number allowing identification of the construction product:
[4552 / 25505,](#)
3. Intended use(s):
[Polyvinyl chloride floor covering for indoor use in compliance with the harmonized standard EN 14041:2004.](#)
4. Name and contact address of the manufacturer:
[2 Avenue François SOMMER F-08203 Sedan Cedex, France](#)
5. System(s) of assessment and verification of constancy of performance:
System 3: Reaction to fire
[Reaction to fire: LNE, notified body N° 0071, carried out testing and provided test report N° N070367-DE/8 according to system 3.](#)
System 4: Other performance
6. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
A – Reaction to fire	Bfl s1	glued on an A1fl and / or A2fl substrate.	EN 14041:2004
	NPD	loose-laid on an A1fl and/or A2fl substrate.	
	Cfl S1	glued on a wooden sub-floor.	
	NPD	loose-laid on a wooden sub-floor.	
B – Content of pentachlorophenol	<5ppm		
C – Formaldehyde emission	E1		
D – Water-tightness	classification of EN 13553		
E – Slipperiness	DS		
F – Antistatic performance	< 2kV		
G – Electrical resistance	≥10E9Ω		
H – Thermal resistance	0.04 m² K/W		

The performance of the product identified above is in conformity with the declared performances. According to the regulation (EU) n°305 / 2011, the present declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Edgard Houssine , Plant Manager
FR-Sedan, 4/1/2013



Signature
