

**PRODUCT
SPECIFICATION
SHEET**



THE ULTIMATE
FLOORING EXPERIENCE

**Permastone® Tile
Luxury Vinyl Flooring**

PRODUCT SPECIFICATIONS

16"x16"

12"x12"

Wearlayer:	Tritonite™ (Urethane)	Tritonite™ (Urethane)
Nominal Thickness:	.125" (3.1 mm)	.125" (3.1 mm)
Gloss:	Matte Satin	Matte Satin
Edge Treatment:	GroutFit®, GroutLess™ and GroutFil™	GroutFit®, GroutLess™ and GroutFil™
Square Feet per Carton:	26.7	27
Weight per Carton (Lbs.):	32	31
Cartons per Pallet:	48	81
ASTM F-970 Static Load Limit:	250 lbs/in ² (113.4 kg)	250 lbs/in ² (113.4 kg)
ASTM E-648 Flooring Radiant Panel	Class 1	Class 1
ASTM E-662 Smoke Density:	<450	<450
FloorScore® Certification SCS-EC10.2-2007:	SCS-FS-01338	SCS-FS-01338
Design Available:	Biscayne, Bombay, Classic Slate, Firenze, Glaze, Indian Slate, Limestone, Modern Slate, Natural Slate, Travertine, Tumbled Marble, Solids	Classic Slate, Solids
SPECIFI Designs Available:	Ferro Stone, Limestone, Modern Slate, Taos	



INSTALLATION

Use:	Residential and Light Commercial
Location:	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
Adhesive:	Tarkett QBond-One™
Adhesive Application:	Residential Dry Set – Apply adhesive with a 1/16" deep x 1/16" wide x 1/16" apart square notched trowel or medium nap paint roller and allow adhesive to dry until it is tacky to the touch. Light Commercial Dry Set - Apply adhesive with a 1/16" deep x 1/16" wide x 1/16" apart notched trowel. Place flooring into adhesive once it has dried and is tacky to the touch.

- Maintain the work area, flooring and adhesive between 65° F and 85° F (18°C - 30°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Use only cementitious based patching and leveling compounds.
- Cartons shall be stored horizontally at all times.
- To ensure the best color match when installing two or more cartons, make sure run numbers on each carton are the same.
- Tarkett QBond-One is used as a dry-set application only in residential applications, and is used as a wet-set application in light commercial settings.
- Roll flooring in both directions with a 75 lbs. (34 kg) 3-section floor roller.
- Refer to Tarkett Luxury Flooring Installation Manual for complete and detailed installation instructions.

CARE AND MAINTENANCE

- **Do not was floor for 48 hours after installation.**
- Do not replace frequently moved furniture or allow heavy traffic for at least 24 hours
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. **Do not use felt pads.**
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.

LIFETIME LIMITED RESIDENTIAL EXTREME PERFORMANCE WARRANTY, 5 YEAR LIMITED LIGHT COMMERCIAL

- The following categories are covered for a residential usage with a lifetime limited warranty for as long as the original purchaser owns the flooring. Proof of purchase is required for claim submittal. Please refer to our Consumer Protection Guide on TarkettNA.com for complete information.

Residential Limited Warranty		Light Commercial Limited Warranty
Wear and Manufacturing Defects	Rip, Tear, Gouge and Indent	Wear
Traffic/Asphalt Stain	Common Household Product Stain	Manufacturing defects
Moisture Stain (Concrete only)	Shoe Scuff	