

PRODUCT SPECIFICATION SHEET



THE ULTIMATE
FLOORING EXPERIENCE

Transcend® Luxury Flooring FreeSpan™ Locking Technology



PRODUCT SPECIFICATIONS

5.04"x36.85"

11.72"x23.72"

Wearlayer:	Urethane	Urethane
Nominal Thickness:	.157" (4 mm)	.158" (4.01 mm)
Gloss:	Matte Satin	Matte Satin
Edge Treatment:	Microbevel	Microbevel
Planks per Carton:	15	
Square Feet per Carton:	19.35	
Weight per Carton (Lbs.):	29.7	
Cartons per Pallet:	63	
ASTM F-925 Resistance to Chemicals:	Pass	
ASTM F-1514 Heat Stability:	ΔE <8	
ASTM F-1515 Light Stability:	ΔE <8	
ASTM F-2199 Dimensional Stability:	<.020" (0.50mm)	
EN13329(B) Flatness:	<.008" (0.50mm)	
ASTM F-970 Static Load Limit:	250 lbs/in ² (113.4 kg)	
ASTM D-2047 Static Coefficient of Friction:	0.5	
ASTM E-648 Flooring Radiant Panel:	Class 1	
ASTM E-662 Smoke Density:	<450	
FloorScore® Certification		
SCS-EC10.2-2007:	SCS-FS-01338	

INSTALLATION

Use:	Residential and Light Commercial
Location:	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
Installation System:	FreeSpan™ Locking Technology

- Maintain room temperature and flooring between 65° F and 85° F for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Cartons must be stored horizontally at all times.
- Use only cementitious based patching and leveling compounds.
- The substrate must be level within 1/8" in 10 ft and have no more than 1.3mm of deflection.
- Begin installation with the tongue side of the plank facing the starting wall.
- A minimum 1/4" (6.3mm) expansion space is required around the perimeter of the room and all vertical objects.
- Do not use a hammer and tapping block to install Transcend.
- The first and last plank in each row must be at least 12" (30.4cm) in length and offset end joints a minimum of 12" (30.4cm).

CARE AND MAINTENANCE

- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching and indentations, equip tables and chairs with proper floor protectors.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wipe up all spills promptly with a damp cloth or mop.
- Wash floor with Tarkett SureShine Floor Cleaner or equal neutral floor cleaner designed for vinyl flooring.
- The use of non-staining mats can remove dirt and debris in the entryways and help prolong the life of the floor.
- Maintain post installation temperature between 55° F and 100° F. Maintain relative humidity between 40% and 70%.

LIFETIME LIMITED RESIDENTIAL WARRANTY, 10 YEAR LIMITED COMMERCIAL WARRANTY

- The following categories are covered for a residential usage with a lifetime limited warranty for as long as the original purchaser owns the flooring. Proof of purchase is required for claim submittal. Please refer to our Consumer Protection Guide on TarkettNA.com for complete information.

Residential Limited Warranty		Commercial Limited Warranty
Wear and Manufacturing Defects	Rip, Tear, Gouge and Indent	Wear
Traffic/Asphalt Stain	Common Household Stain	Manufacturing defects
Moisture Stain (Concrete only)	Shoe Scuff	