



## Trends 12 ® Laminate Flooring

## Product Specifications

| PRODUCT DETAILS                                     | Royal Oak  | Factor 6  |
|---|--|---|
| <b>Item Number:</b>                                 | 33799244096<br>33799244089<br>33799224654<br>33799225170 | 33799218387<br>33799218295<br>33799218318<br>35010130253<br>35020125035 |
| <b>Thickness:</b>                                   | 1/2" (12 mm)   | 1/2" (12 mm)  |
| <b>Width:</b>                                       | 7-4/5" (19.81 cm)  | 7-18/25" (19.61 cm),<br>5-16/25" (14.33 cm),<br>3-14/25" (9.04 cm)      |
| <b>Length:</b>                                      | 47-7/8" (1.22 m)   | 23-3/5" (59.94 cm),<br>47-7/8" (121.6 cm)                               |
| <b>Edges:</b>                                       | Bevel  | Bevel   |
| <b>Wear Resistance:</b>                             | AC3  | AC3   |
| <b>CARB II Compliant:</b>                           | Yes  | Yes   |
| <b>Planks per Carton:</b>                           | 6  | 15 (various sizes)<br>Contact Tarkett<br>Technical for details.         |
| <b>Square Feet per Carton:</b>                      | 15.47 (1.44 m <sup>2</sup> )                             | 22.39 (2.08 m <sup>2</sup> )  |
| <b>Weight per Carton</b>                            | 32 Lbs. (14.52 kg)                                       | 47 Lbs. (21.32 kg)  |
| <b>Cartons per Pallet:</b>                          | 65   | 39  |
| <b>Floorscore® Cert.</b><br>SCS-EC10.3-2014<br>v4.0 | Yes  | Yes   |

- 1. INSTALLATION** - See package insert for complete Installation Information.

**Use:** Residential, and Light Commercial

**Installation System:** T-Lock, Angle-Drop

**Location:** Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Tarkett laminate flooring shall acclimate to the temperature of the room. Place unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity shall be between 40% and 70%.
- Substrate shall be level to within 1/4" in 8 feet (6.35 mm in 2.4 m).
- Install approved laminate foam underlayment. Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 40' (12m) in length or width will require the use of Tarkett T-Molding.
- Planks are installed by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Position the plank so it is aligned with the short side of the previous plank. Rotate the plank downward to engage the long and short side joints.
- The first and last plank in each row shall be at least 12" (30.4 cm) in length. Stagger end joints a minimum of 12" (30.4 cm).

- 2. WARRANTY** - See package insert for complete Warranty Information.

- 25 YEAR LIMITED RESIDENTIAL WARRANTY
- 5 YEAR LIMITED LIGHT COMMERCIAL

- 3. CARE AND MAINTENANCE**

- Post installation temperature must be maintained between 65°F and 85°F. Relative humidity must be maintained between 40% and 70%.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching, equip tables and chairs with proper floor protectors.
- To help prolong the life of the floor, use walk-off mats at outside entrances to collect dirt and debris and excess moisture.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wipe up all spills promptly with a dry cloth.
- When necessary, lightly damp mop floor with Tarkett SureShine Floor Cleaner or equal neutral floor cleaner. Do not use excessive water when cleaning.



### Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

888-639-8275 Fax 440-498-0025

northamerican.technicalsupport@tarkett.com

[www.tarkettna.com](http://www.tarkettna.com)