



Aloft® Floating Floors FreeSpan™ Locking Technology

Product Specification

1. PRODUCT DETAILS

- **Wear layer:** .012" (.3mm)
- **Nominal Thickness:** .126" (3.2mm)
- **Gloss:** Matte
- **Edge Treatment:** Slight Microbevel
- **Planks per Carton:** 14
- **Square Feet per Carton:** 27.58
- **Weight per Carton (Lbs.):** 34.17
- **Cartons per Pallet:** 60

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Dimensional Stability:** ASTM F2199: Passes
- 2.2. **Heat Stability:** ASTM 1514: $\Delta E \leq 8$
- 2.3. **Light Stability:** ASTM F1515: $\Delta E \leq 8$
- 2.4. **Stain Resistance:** ASTM F925: Passes
- 2.5. **Slip Resistance:** ASTM D2047: SCOF ≥ 0.5
- 2.6. **Fire Performance:** ASTM E648: Class 1
- 2.7. **Smoke Density:** ASTM E-662: <450
- 2.8. **Static Load Limit:** ASTM F-970: Passes
- 2.9. **FloorScore® Certification:** Yes

3. INSTALLATION – Refer to Detailed Installation

Instructions at www.tarkettna.com

- Maintain the work area between 55° F and 95° F (12°C - 35°C) for 48 hours before and during Installation. Refer to Installation Instructions for complete details regarding applications with and without permanent HVAC controls.
- Cartons shall be stored horizontally on a sturdy base at all times.
- Aloft® and ProSheet Plus 3 is an acceptable installation system. (Follow ProSheet Plus 3 Installation Instructions).
- Aloft® and SureStart Underlayment is an acceptable installation system. (Follow SureStart Underlayment Installation Instructions).
- The substrate must be level within 1/8" in 10 ft and have no more than 1.3mm of deflection.
- Begin installation with the tongue side of the plank facing the starting wall.
- A minimum 1/4" (6.3mm) expansion space is required around the perimeter of the room and all vertical objects.
- Do not use a hammer and tapping block to install Aloft.
- The first and last plank in each row must be at least 12" (30.4cm) in length and offset end joints a minimum of 12" (30.4cm).

4. WARRANTY –For complete details, contact Tarkett Technical Services or go to www.tarkettna.com

- 25 YEAR RESIDENTIAL LIMITED WARRANTY
- 7 YEAR LIGHT COMMERCIAL LIMITED WARRANTY

5. MAINTENANCE

- 5.1. Furniture can be replaced immediately after installation.
- 5.2. Never slide heavy furniture or appliances across the floor. Place sheets of plywood over finished floor when moving furniture and appliances into position.
- 5.3. Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- 5.4. Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- 5.5. Clean floor using Tarkett SureShine® Floor Cleaner or an equivalent pH neutral floor cleaner. Follow manufacturers label instructions for precaution and use.

7. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8297.



Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275 Fax 440-498-0025
northamerican.technicalsupport@tarkett.com

www.tarkettna.com