



## Aloft™ Glue-Down Luxury Vinyl Flooring

## Product Specification

**Aloft Glue-Down Luxury Vinyl Flooring.** Affordable beauty engineered to withstand the demands of a busy home. Aloft is backed by a 25-Year Residential Limited Warranty and a 7-year Light Commercial Limited Warranty.

### 1. PRODUCT DETAILS

**Nominal Thickness:** 0.80" (2 mm)  
**Wearlayer:** 12 Mills (0.2mm) Urethane Protection System  
**Edge Treatment:** Square Edge  
**Plank Size:** 6" x 48" (15.24 cm x 121.92 cm)  
**Sq. Ft. per Carton:** 36 (3.34 m<sup>2</sup>)  
**Planks per Carton:** 18  
**Cartons per Pallet:** 78  
**Weight per Carton:** 42.99 lbs. (19.49 kg)

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1 **ASTM E648 (Fire):**  $\geq 0.45$  w/cm<sup>2</sup>; Class 1  
2.2 **ASTM E662 (Smoke):**  $\leq 450$   
2.3 **Stain Resistance:** ASTM F925: Passes  
2.4 **Static Load:** ASTM F970: Passes  
2.5 **Heat Stability:** ASTM 1514:  $\Delta E \leq 8.0$   
2.6 **Light Stability:** ASTM F1515:  $\Delta E \leq 8.0$   
2.7 **FloorScore® Certification:** SCS-EC10.3-2014 v4.0

### 3. INSTALLATION – Refer to Detailed Installation

Instructions at [www.tarkettna.com](http://www.tarkettna.com)

- Maintain the work area between 65° F and 85° F (18°C - 30°C) for 48 hours before and during and after Installation. Maintain relative humidity between 40% and 70%.
- Cartons shall be stored horizontally on a sturdy base at all times.
- Aloft™ and ProSheet Plus 3 is an acceptable installation system. (Follow ProSheet Plus 3 Installation Instructions).

### 4. ADHESIVE

#### Tarkett QBond-One Adhesive

Releasable - Medium Nap Roller

Permanent – Non-porous 1/32" x 1/16" x 1/32" U notch trowel  
Porous-1/16" x 1/16" x 1/16" V notch trowel

#### Tarkett 959 Vinyl Tile and Tile Adhesive

Permanent - Porous: 1/16" x 1/16" x 1/16" V-notch or  
Non-porous: 1/32" x 1/16" x 1/32" U-notch  
Porous/Non-porous: Medium Nap Roller

### 5. WARRANTY –For complete details, contact Tarkett Technical Services or go to [www.tarkettna.com](http://www.tarkettna.com)

- 25 YEAR EXTREME PERFORMANCE RESIDENTIAL WARRANTY
- 7 YEAR LIGHT COMMERCIAL LIMITED WARRANTY

### 6. MAINTENANCE

- 6.1. Do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- 6.2. Do not wash floor for 48 hours after installation
- 6.3. Never slide heavy furniture or appliances across the floor. Place sheets of plywood over finished floor when moving furniture and appliances into position.
- 6.4. Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- 6.5. Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- 6.6. Clean floor using Tarkett SureShine® Floor Cleaner or an equivalent pH neutral floor cleaner. Follow manufacturers label instructions for precaution and use.

### 7. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at (888)-639-8297.

