



Fresh Air™ Laminate Flooring

Product Specifications

Product Details	Ridgeway Hickory	All Others
Item Number	35030117181, 35030117183, 35030117182	35030187617, 35030187618, 35030129413, 35030129405, 35030106006, 35030106820, 35030121512
Thickness	1/2" (12 mm)	1/2" (12mm)
Width	7-5/8" (195mm) 4-3/8" (110mm)	7-18/25" (196mm) 3-11/16" (94mm)
Length	47-7/8" (1203mm)	47-7/8" (1216mm)
Edges	4 sided eased edge	4 sided bevel
Wear Resistance	AC3	AC3
CARB II Compliant	Yes	Yes
Planks per Carton	12	12
SQ FT per Carton	23.82 (2.21 m ²)	23.82 (2.21 m ²)
Weight per Carton	49.5 (22.5 kg)	47.8 (21.7 kg)
Cartons per Pallet	39	39

1. INSTALLATION - See package insert for complete Installation Information.

Use: Residential
Installation System: T-Lock, Angle-Drop
Location: Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Tarkett laminate flooring shall acclimate to the temperature of the room. Place unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity shall be between 40% and 70%.
- Substrate shall be level to within 1/4" in 8 feet (6.35 mm in 2.4 m).
- Install approved laminate foam underlayment. Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 40' (12m) in length or width will require the use of Tarkett T-Molding.
- Planks are installed by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Position the plank so it is aligned with the short side of the previous plank. Rotate the plank downward to engage the long and short side joints.
- The first and last plank in each row shall be at least 12" (30.4 cm) in length. Stagger end joints a minimum of 12" (30.4 cm).

2. WARRANTY - See package insert for complete Warranty Information.

- 25 YEAR RESIDENTIAL WARRANTY
- 5 YEAR LIGHT COMMERCIAL WARRANTY

3. CARE AND MAINTENANCE

- Post installation temperature must be maintained between 65°F and 85°F. Relative humidity must be maintained between 40% and 70%.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching, equip tables and chairs with proper floor protectors.
- To help prolong the life of the floor, use walk-off mats at outside entrances to collect dirt and debris and excess moisture.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wipe up all spills promptly with a dry cloth.
- When necessary, lightly damp mop floor with Tarkett SureShine Floor Cleaner or equal neutral floor cleaner. Do not use excessive water when cleaning.



Tarkett North America

Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 888-639-8275 Fax 440-498-0025
 northamerican.technicalsupport@tarkett.com

www.tarkettna.com