

# PRODUCT SPECIFICATION SHEET



THE ULTIMATE FLOORING EXPERIENCE

## Heritage Laminate Flooring

### PRODUCT SPECIFICATIONS

<b>Item Number:</b>	42138383, 42138382, 42139385	42140380
<b>Thickness:</b>	5/16" (8 mm)	5/16" (8 mm)
<b>Width:</b>	7 5/8" (19.41 cm)	7 5/8" (19.41 cm)
<b>Length:</b>	50 7/8" (1.3 m)	50 7/8" (1.3 m)
<b>Edges:</b>	Microbevel	Long Side Bevel
<b>Wear Resistance:</b>	AC4	AC4
<b>CARB II Compliant:</b>	Yes	Yes
<b>Planks per Carton:</b>	8	8
<b>Square Feet per Carton:</b>	21.59 (2.01 m <sup>2</sup> )	21.59 (2.01 m <sup>2</sup> )
<b>Weight per Carton (Lbs):</b>	32 (14.52 kg)	32 (14.52 kg)
<b>Cartons per Pallet:</b>	56	56



### INSTALLATION

<b>Use:</b>	Residential, Light Commercial, and Commercial
<b>Installation System:</b>	T-Loc Angle-Drop (5G)
<b>Location:</b>	Below, on, and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Tarkett laminate flooring shall acclimate to the temperature of the room. Place unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity shall be between 40% and 70%.
- Substrate shall be level to within 1/4" in 8 feet (6.35 mm in 2.4 m).
- Install approved laminate foam underlayment. Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 40' (12m) in length or width will require the use of Tarkett T-Molding.
- Planks are installed by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Position the plank so it is aligned with the short side of the previous plank. Rotate the plank downward to engage the long and short side joints.
- The first and last plank in each row shall be at least 12" (30.4 cm) in length. Stagger end joints a minimum of 12" (30.4 cm).

### CARE AND MAINTENANCE

- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Never move heavy furniture or appliances directly across laminate flooring. Place sheets of plywood over laminate when moving heavy furniture or appliances into position.
- Use smooth, hard plastic or metal furniture rests or glides with a bearing surface of 1" or larger under frequently moved furniture to avoid scratches and indentations. **Do not use felt pads.**
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris.
- Sweep or vacuum (do not use beater bar) laminate floor to remove dirt and debris that can cause scratches or dull the finish.
- Clean up all spills immediately with a damp cloth. Do not allow liquids to remain on laminate flooring.
- Periodically damp mop laminate floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly. Do not use soap or oil based cleaning products. Do not use abrasive cleaners, steel wool or scouring powder.
- Do not flood the laminate floor with water or put water or any other liquids directly on the floor. Excessive water will damage your floor, resulting in peaked edges, warping, swelling and delamination.

### LIFETIME LIMITED RESIDENTIAL, 15 YEAR LIMITED LIGHT COMMERCIAL, AND 10 YEAR COMMERCIAL

- The following categories are covered for a residential usage with a lifetime limited warranty for as long as the original purchaser owns the flooring. Proof of purchase is required for claim submittal. Please refer to the carton insert for complete information.

RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
Wear, Stain, or Fade from Light	Wear	Wear
Manufacturing Defects	Manufacturing Defects	Manufacturing Defects