

PRODUCT SPECIFICATION SHEET



THE ULTIMATE FLOORING EXPERIENCE

Trends™ Laminate Flooring



PRODUCT SPECIFICATIONS

Item Number:	35010180962, 35010198886, 35010101711, 35010111721, 35010178416	35010188843, 35010188844, 35010188841, 35010192991
Thickness:	7/16" (10 mm)	7/16" (10mm)
Width:	3-3/4" (9.5 cm)	5" (12.7 cm)
Length:	47 5/8" (1.2 m)	47 5/8" (1.2 m)
Edges:	Bevel	Bevel
Wear Resistance:	AC3	AC3
Indentation Class:	IC3	IC3
CARB II Compliant:	Yes	Yes
Planks per Carton:	14	10
Square Feet per Carton:	17.21 (1.59 m ²)	16.48 (1.53 m ²)
Weight per Carton (Lbs):	32.4 (14.6 kg)	32 (14.5 kg)
Cartons per Pallet:	65	63

INSTALLATION

Use:	Residential, Light Commercial, and Commercial
Installation System:	T-Loc Angle-Drop
Location:	Below, on, and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Tarkett laminate flooring shall acclimate to the temperature of the room. Place unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity shall be between 40% and 70%.
- Substrate shall be level to within 1/4" in 8 feet (6.35 mm in 2.4 m).
- Install approved laminate foam underlayment. Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 40' (12m) in length or width will require the use of Tarkett T-Molding.
- Planks are installed by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Position the plank so it is aligned with the short side of the previous plank. Rotate the plank downward to engage the long and short side joints.
- The first and last plank in each row shall be at least 12" (30.4 cm) in length. Stagger end joints a minimum of 12" (30.4 cm).

CARE AND MAINTENANCE

- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Never move heavy furniture or appliances directly across laminate flooring. Place sheets of plywood over laminate when moving heavy furniture or appliances into position.
- Use smooth, hard plastic or metal furniture rests or glides with a bearing surface of 1" or larger under frequently moved furniture to avoid scratches and indentations. **Do not use felt pads.**
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris.
- Sweep or vacuum (do not use beater bar) laminate floor to remove dirt and debris that can cause scratches or dull the finish.
- Clean up all spills immediately with a damp cloth. Do not allow liquids to remain on laminate flooring.
- Periodically damp mop laminate floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly. Do not use soap or oil based cleaning products. Do not use abrasive cleaners, steel wool or scouring powder.
- Do not flood the laminate floor with water or put water or any other liquids directly on the floor. Excessive water will damage your floor, resulting in peaked edges, warping, swelling and delamination.

25 YEAR LIMITED RESIDENTIAL AND 5 YEAR LIMITED LIGHT COMMERCIAL

- The following categories are covered for a residential usage with a 25 year limited warranty for as long as the original purchaser owns the flooring. Proof of purchase is required for claim submittal. Please refer to the carton insert for complete information.

RESIDENTIAL	COMMERCIAL
Wear, Stain, or Fade from Light	Wear
Manufacturing Defects	Manufacturing Defects