



# HOMOGENEOUS SHEET/TILE FLOORING

## Standard Plus

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Homogeneous sheet and tile floor coverings, non-directional patterned, designed for durability and commercial interiors.

1.2. Recommended areas for use:

- Healthcare – Patient rooms, exam rooms, lobbies, corridors, emergency rooms, critical care, laboratories
- Education – Classrooms, corridors, multipurpose rooms, gymnasiums, laboratories, cafeterias
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Hospitality – Corridors, vending areas, lobbies, bathrooms

1.3. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Option 3
Web: <a href="http://www.tarkettna.com">www.tarkettna.com</a>	Samples: Option 1
E-mail: <a href="mailto:info@johnsonite.com">info@johnsonite.com</a>	

1.4. Proprietary Product Description:

Construction: Standard Plus is composed of a tough, UV-cured factory applied polyurethane finish (PU) on a homogenous vinyl construction.

1.4.1. Styles:

- Standard Plus (Rolls and Tiles)
- Rolls available in 6' 6" (2 m) wide nominal, 75' 9" (23 linear meters), & approximately 5.8 lbs/yd<sup>2</sup> (3.1 kg/m<sup>2</sup>)
- Tiles sizes/packaging:
  - 24" x 24" (61 cm x 61 cm), 14 pc/carton, 56 ft<sup>2</sup> (5.20 m<sup>2</sup>), & 36.12 lbs/carton (16.4 kg)
  - 12" x 12" (30 cm x 30 cm), 60 pc/carton, 60 ft<sup>2</sup> (5.57 m<sup>2</sup>), & 39.3 lbs/carton (17.82 kg)
  - 12" x 24" (30 cm x 61 cm), 28 pc/carton, 56 ft<sup>2</sup> (5.20 m<sup>2</sup>), & 36.12 lbs per carton (16.4 kg)

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Products meets the following performance criteria of ASTM F 1913 Standard Specification for Vinyl Sheet Floor Covering without Backing.
- 2.2. Polyurethane Reinforced (ASTM F 410): Yes
- 2.3. Tile Squareness (ASTM F 2055): Passes
- 2.4. Tile Dimensional Stability (ASTM F 2199): Passes
- 2.5. Flexibility (ASTM F137): Passes
- 2.6. Total Thickness (ASTM F 386): 0.080 in. (2 mm)
- 2.7. Static Load Limit (ASTM F 970): Passes

2.8. Resistance to Heat (ASTM F 1514):  $\Delta E \leq 8$

2.9. Resistance to Light (ASTM F 1515):  $\Delta E \leq 8$

2.10. Slip Resistance (ASTM D 2047): SCOF  $\geq 0.5$

2.11. Fire Performance (ASTM E648 Flooring Radiant Panel): Class 1

2.12. Smoke Density (ASTM E 662):  $\leq 450$

2.13. Chemical Resistance (ASTM F925): Passes

### 3. INSTALLATION

See homogeneous sheet or tile flooring installation instructions for complete details.

3.1. Roll Adhesives:

- Tarkett 925 Adhesive Coverage:
  - Porous Substrate: 250-300 sq. ft./gal.
  - Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive Coverage:
  - Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- Tarkett RollSmart Adhesive Coverage:
  - 350 - 400 sq. ft. per gallon
  - (3/8" Nap Paint Roller used with a paint tray)
- Tarkett 901 SpraySmart Adhesive Coverage:
  - 150 sq. ft. per. Container
- Tarkett Cold Weld Liquid Coverage: 175 – 200 lin. ft. per. 4.5 oz. tube

3.2. Tile Adhesives:

- Tarkett 926 Adhesive Coverage:
  - Porous & Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive Coverage:
  - Porous & Non-porous Substrate: 250-300 sq. ft. per gallon

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Standard Plus Maintenance Instructions for complete maintenance details.



THE ULTIMATE  
FLOORING EXPERIENCE

**Technical Services Department**  
 30000 Aurora Road, Solon, Ohio 44139  
 (800) 899-8916 ext 9297  
 Fax (440) 632-5643  
 email: [info@johnsonite.com](mailto:info@johnsonite.com)  
[www.tarkettna.com](http://www.tarkettna.com)





# HOMOGENEOUS SHEET/TILE FLOORING

Standard Plus

Product Specification

## 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarketta.com](http://www.tarketta.com) or contact Tarkett at 1-800-899-8916.



THE ULTIMATE  
FLOORING EXPERIENCE

**Technical Services Department**  
30000 Aurora Road, Solon, Ohio 44139  
(800) 899-8916 ext 9297  
Fax (440) 632-5643  
email: [info@johnsonite.com](mailto:info@johnsonite.com)  
[www.tarketta.com](http://www.tarketta.com)