

VINYL COMPOSITION TILE

Azrock® VCT
Azrock® TexTile

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. Proprietary Product: Vinyl Composition Tiles designed for durability and commercial interiors.
- 1.2. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: www.tarkettna.com	Samples: Ext 9299
E-mail: info@johnsonite.com	
- 1.3. Proprietary Product Description:
 - 1.3.1. Construction: Azrock VCT and Azrock TexTile VCT are manufactured from a homogeneous composition of high quality additives, and colorants to meet the performance requirements of ASTM F 1066, Standard Specification for Vinyl composition Tile, Class 2 (Through pattern) and Class 1 (Solid Color).
 - 1.3.2. Styles:
 - V-XXX (Azrock VCT & Azrock TexTile)
 - 1.3.3. Physical Characteristics:
 - Overall thickness: 1/8" (3.17 mm)
 - Size: 12" X 12" (30.5 cm x 30.5 cm)
 - Quantity: 45 tiles / carton
 - 45 sq. ft. (4.18 m²) / carton
 - Weight: 1.4 lbs. / sq. ft. (64 lbs. / carton)
2. PRODUCT PERFORMANCE AND TECHNICAL DATA
 - 2.1. Heat Stability (ASTM F 1514): $\Delta E \leq 8$
 - 2.2. Size/Squareness (ASTM F2055): Passes
 - 2.3. Deflection (ASTM F1304): Passes
 - 2.4. Impact Resistance (ASTM F1265): Passes
 - 2.5. Dimensional Stability (ASTM F2199): Passes
 - 2.6. Chemical Resistance (ASTM F925): Passes
 - 2.7. Static coefficient of friction (ASTM D 2047): 0.5 SCOF
 - 2.8. Residual Indentation (ASTM F1914): Conforms
 - 2.9. Static Load Limit (ASTM F 970): Passes 150 psi with less than 5 mils (0.005") residual indentation
 - 2.10. Fire Performance (ASTM E 648 Flooring Radiant Panel): Class 1

3. INSTALLATION

See Vinyl Composition Tile flooring installation instructions for complete details.

3.1. Adhesive:

- Tarkett 100 Clear Thin Spread Adhesive Coverage:
Porous Substrate: 250-300 sq. ft./gal.
- Tarkett 975 Two-Part Polyurethane Adhesive Coverage:
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- Tarkett 901 SpraySmart Adhesive Coverage:
200 sq. ft. per. container (1,200 sq. ft. per carton)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Vinyl Composition Tile Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
30000 Aurora Road, Solon, Ohio 44139
(800) 899-8916 ext 9297
Fax (440) 632-5643
email: info@johnsonite.com
www.tarkettna.com