

WOOD

ELEGANCE

PRODUCT DATASHEET 2017



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Protecto Hardwax Oil	EN 13696	N/A
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,152 0,182 0,192
Thermal conductivity (W/m K) 22 mm	EN 12664 / EN 14342:2013	0,105
Breaking strength	EN 1533	6480 N / 600mm

INSTALLATION	
Installation method	On beams or glue down
Installation instruction	Download from tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes


RECOMMENDED ACCESSORIES	
Installation	Adhesive as recommended in installation instruction. Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Hardwax Oil Refresher Hardwax Oil
See more alternatives and the complete range of accessories @ www.tarkett.com	

SIZE AND PACKAGE	22x260x2520	22x280x2520
Thickness (mm)	22	22
Width (mm)	260	280
Length (mm)	2520	2520
Wear layer thickness (mm)	4,0	4,0
Boards/pack	4	4
m ² /pack	2,62	2,82
m ² /pallet	31,44	33,84
Weight/m ² (kg)	11,7	11,7

Due to the nature of the material this table shows typical values.

MAINTENANCE
Tarkett wooden floors have a Protecto surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Elegance Protecto Hardwax Oil



WOOD

ELEGANCE

DESIGN

Oak Planks made extra wide and extra long to enhance their natural look, mixing the smooth and more distinctive details of the wood. A light brushing emphasizes the design and authentic structure of the material. Perfect for special installations and commercial applications, where exclusivity and durability are the key requirements.

PRODUCT DATA	Material code	Size (mm)			Pattern	Surface treatment	Surface effect	Bevel (4 side)	Stained	DoP no.
		Thickness	Width	Length						
Elegance Oak Champagne	41008002	22	280	2 520	1-strip	Protecto Hardwax Oil	Brushed	Minibevel	Yes	0190-0116
	41008005	22	260	2 520	1-strip		Brushed	Minibevel	Yes	0190-0116
Elegance Oak Sterling	41008004	22	280	2 520	1-strip		Brushed	Minibevel	Yes	0190-0116
Elegance Oak	41008001	22	280	2 520	1-strip		Brushed	Minibevel	No	0190-0116



Elegance Oak Champagne



Elegance Oak Sterling



Elegance Oak

The pictures only present the color of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.

For further and latest information please visit www.tarkett.com