

# Omnisports EXCEL



## KEY POINTS

### Description :

Vinyl sports floor covering over fibreglass with PVC foam backing. Protected with Top Clean XP® (dirt-resistant treatment for ease of maintenance)

### 3 types of installation :

- Loose laid
- Glued Installation
- Installation over a Tarkolay

### Surface Texture : Sorrent

### Installation instructions and maintenance guide :

On request

### Dimensions (EN ISO 24341) :



2 m



20.5 lm or 23 lm

### Total thickness (EN ISO 24346) :



8.3 mm (± 0,2mm)

### Total weight (EN ISO 23997) :



6.15 kg/m<sup>2</sup> (± 800g)

Technical data in force as from the date of publication (02/2016).

The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement.

For more detailed technical information, please contact Tarkett.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.

Properties	Standards	Omnisports EXCEL
------------	-----------	------------------

Sports properties		
Friction	EN 13036-4	80 - 110
Shock absorption	EN 14 808	P1
Vertical deformation	EN 14 809	
Vertical ball rebound	EN 12235	compliant

Classification		
Reaction to fire	EN 13501-1	Cfl-S1

Technical Characteristics		
Wear Layer	EN 429	0.80 mm
Resistance to wear	EN ISO 5470-1	≤ 1g
Resistance to indentation	EN 1516	compliant < 0.50mm
Behaviour under a rolling load	EN 1569	< 0.50mm No degradation
Resistance to impact	EN 1517	No degradation

Specific Characteristics		
Surface treatment	Topclean X-treme performance protection	
Maintenance		

**COMPATIBLE SLABS:** Concrete, asphalt screed, anhydrite screed. Any deviation of the slab must be corrected prior installation (6 mm under a 3m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards.

## Omnisports Excel



Tarkett France – 1 terrasse Bellini – Tour Initiale TSA 94200 - 92919 Paris la Défense CEDEX  
 TÉL. +33(0)1 41 20 40 40 – FAX +33(0)1 41 20 47 05 – info@tarkett.com  
 www.professionals.tarkett.com