

PROFESSIONAL

WOOD - PRODUCT DATASHEET 2019



TECHNICAL DATA (EN 13489)		13 mm	14 mm	22 mm
Reaction to fire	EN 14342 Table 1 (when applicable) / EN 13501	Dfl-s1		
Emission of formaldehyde	EN 14342	E1		
Brinell hardness (average value) Oak Ash	(BHN) EN1534	3,7 4,0		
Taber Abraser/Lacquer's wear resistance Protoco Lacquer Protoco Natura <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	4000 3500		
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17		
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141	0,152 0,182 0,192	
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,104	0,11	0,136

INSTALLATION		
Installation method 10 - 14 mm 22 mm	Floating or glue down Floating, nailed or glue down	
Installation instruction	Download from www.tarkett.com Contact your supplier for more details	
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes	
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²		

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting, Transition moulding, Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean, Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

DIMENSIONS & PACKAGE	13x194x2027	14x194x2027	22x194x2535
Thickness EN 13489 (mm)	13	14	14
Width (mm)	194	194	194
Length (mm)	2027	2027	2535
Wear layer thickness (mm)	2,5	3,5	3,5
Boards/pack	6	6	4
m ² /pack	2,36	2,36	1,97
m ² /pallet	94,40	94,40	68,95
Net weight/m ² (kg)	7,3	7,9	10,6
Due to the nature of the material this table shows typical values.			

MAINTENANCE
Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Professional 13-14mm
Protoco Lacquer / Protoco Natura

98 % 98 % Natural Renewable	100 % Recyclable
--------------------------------------	---------------------



2-LOCK



T&G



Protoco

Professional 22 mm
Protoco Lacquer

99 % 99 % Natural Renewable	100 % Recyclable
--------------------------------------	---------------------



www.realwood.eu



SILVER

PROFESSIONAL

WOOD - PRODUCT DATASHEET 2019

DESIGN

Real wooden floors for special applications.

PRODUCT DATA	Material code	Dimensions (mm)			Pattern	Surface treatment	Surface effect	Bevel	Stained	DoP no.
		Thickness	Width	Length						
PROFESSIONAL 13 MM										
Oak Nature	8722011	13	194	2 027	3-strip	Proteco Lacquer	-	-	No	0020-0104
	8722002	13	194	2 027	3-strip	Proteco Natura	-	-	No	0020-0104
PROFESSIONAL 14 MM										
Oak Nature	8721001	14	194	2 027	3-strip	Proteco Lacquer	-	-	No	0020-0106
	8721002	14	194	2 027	3-strip	Proteco Natura	-	-	No	0020-0106
PROFESSIONAL 22 MM										
Oak Nature	7825011	22	194	2 535	3-strip	Proteco Lacquer	-	-	No	0020-0117

PROFESSIONAL 13/14 MM



Oak Nature

PROFESSIONAL 22 MM



Oak Nature

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.

For further and latest information please visit www.tarkett.com