

WOOD Product Datasheet 2016



TECHNICAL DATA (EN 14354)		
Reaction to fire	EN 13501-1	Dfl-s1
Emission of formaldehyde	EN 13986	E1
Brinell hardness (average value)	(BHN) EN1534	6,0
Taber Abraser/Lacquer's wear resistance Protoco Lacquer Protoco Natura <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	4000 3500
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,054 0,074 0,094
Thermal conductivity (W/m K) 8,5 mm	EN 12664 / EN 14342:2013	0,14

INSTALLATION	
Installation method	Floating or glue down
Installation instruction	Download from tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

SIZE AND PACKAGE	8,5x110x1220	8,5x190x1220
Thickness (mm)	8,5	8,5
Width (mm)	110	190
Length (mm)	1220	1220
Wear layer thickness (mm)	0,6	0,6
Boards/pack	12	8
m ² /pack	1,61	1,85
m ² /pallet	67,62	74,00
Weight/m ² (kg)	7,7	7,7

Due to the nature of the material this table shows typical values.

MAINTENANCE
Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com


Viva Protoco Lacquer / Protoco Natura



DESIGN

8.5 mm floor with a thin veneer layer on top of an HDF core, giving you a hard and durable floor with good acoustic comfort.

PRODUCT DATA	Material code	Size (mm)			Pattern	Surface treatment	Surface effect	Bevel (4 side)	Stained	DoP no.
		Thickness	Width	Length						
VIVA										
Viva Ash Design White	7953003	8,5	190	1 220	2-strip	Proteco Lacquer	-	-	Yes	0190-0001
Viva Oak White	7829002	8,5	190	1 220	2-strip	Proteco Natura	-	-	Yes	0190-0001
Viva Oak (1-strip)	7828009	8,5	190	1 220	1-strip	Proteco Natura	Brushed	Microbevel	No	0190-0001
Viva Oak (2-strip)	7828007	8,5	190	1 220	2-strip	Proteco Natura	-	-	No	0190-0001
Viva Oak (3-strip)	7828001	8,5	190	1 220	3-strip	Proteco Lacquer	-	-	No	0190-0001
	7828002	8,5	190	1 220	3-strip	Proteco Natura	-	-	No	0190-0001
Viva Walnut	8581002	8,5	190	1 220	3-strip	Proteco Natura	-	-	No	0190-0001
VIVA LINE										
Viva Line Oak	7831002	8,5	110	1 220	1-strip	Proteco Natura	-	Microbevel	No	0190-0001
Viva Line Oak (brushed)	7831003	8,5	110	1 220	1-strip	Proteco Natura	Brushed	Microbevel	No	0190-0001
Viva Line Walnut	8582002	8,5	110	1 220	1-strip	Proteco Natura	-	Microbevel	No	0190-0001
Viva Line Oak Black	7831004	8,5	110	1 220	1-strip	Proteco Natura	Brushed	Microbevel	Yes	0190-0001



Viva Ash Design White



Viva Oak White



Viva Oak (1-strip)



Viva Oak (2-strip)



Viva Oak (3-strip)



Viva Walnut



Viva Line Oak



Viva Line Oak (brushed)



Viva Line Walnut



Viva Line Oak Black

The pictures only present the color of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com
Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.

For further and latest information please visit www.tarkett.com