

HOMOGENEOUS
COMPACT VINYL

Wallgard

CERTIFICATION & CLASSIFICATION		STANDARDS	Wallgard
Type of wall covering			Homogeneous vinyl wall covering.
CE certification		EN 15102	Yes
ISO certification			Ronneby ISO 9001/Ronneby ISO 14001
TECHNICAL CHARACTERISTICS		STANDARDS	Wallgard
PU-Shield			Yes
Total thickness		ISO 24346 – EN 428	1.3 mm
Total weight/m²		ISO 23997 – EN 430	2100 g
Form of delivery		ISO 24341 – EN 426 Sheet (rolls)	Approx. 30 running metres x 200 cm Art. no. 21055_ _ _ <small>3 digit colour colour number</small>
TECHNICAL PERFORMANCES		STANDARDS	Wallgard
Total VOC emissions		ISO 16000-6 AgBB/DIBt	≤ 10 µg/m ³ (after 28 days) Confirm
Outgassing VOC (23°C/90°C)		ISO-Acc _m class	<- 9.6
Reaction to fire		EN 13501-1 AS/NZS 3837	Class B s2 d0 Class B
Wetroom approval		GBR Class VT	Approved
Airborne particle emissions		ISO 14644-1 ASTM F24 F51	ISO class 4 Class A
Dimensional stability		ISO 23999 – EN 434	≤ 0.40 %
Light fastness		EN ISO 105-B02	≥ level 7
Chemical resistance		ISO 26987 – EN 423	Excellent
Bacteria resistance		ISO 846:Part C	Does not favour growth
Seam strength		EN 684	Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm
Colours			13

The above information is subject to modification for the benefit of further improvement (07/2015).