

HETEROGENEOUS
ACOUSTIC VINYLTapiflex
Evolution

Specification

Acoustic flexible vinyl floorcovering with a new foam backing on a non woven glass fiber stabilized carrier. This HE vinyl is reinforced with TopClean XP™ and built-in fungistatic and bacteriostatic treatment.

Product standard: EN 651.



CERTIFICATION & CLASSIFICATION	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Type of floorcovering	ISO 11638 - EN 651			Heterogeneous acoustic vinyl
Wear Layer Binder Content	ISO 10582			Type I
UPEC Classification	EN ISO 717-2			U4P3E2/3C2
Impact sound reduction	EN ISO 717-2			ΔL_w 17 dB
Acoustical Improvement	NF S31-074			$L_{n,e,w}$ = < 65 dB - Class A
Classification	ISO 10874 - EN 685			34
TECHNICAL CHARACTERISTICS	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Wear layer thickness	ISO 24340 - EN 430	1.00 mm	0.90 mm	0.70 mm
Surface Treatment		TopClean XP™	TopClean XP™	TopClean XP™
Total thickness	ISO 24346 - EN 428	3.35 mm	3.20 mm	3.05 mm
Abrasion Group / mm³	EN 660-2	Group T : ≤ 2.0	Group T : ≤ 2.0	Group T : ≤ 2.0
Total weight / m²	ISO 23997 - EN 430	3570	3440	3210
Form of delivery	ISO 24344 - EN 426 Sheet (rolls)			approx. 23 running metres x 200 cm
TECHNICAL PERFORMANCES	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Dimensional stability	ISO 23999 - EN 434			Length + width < 0.10%
Reaction to fire	EN 13501-1			B _{fl} s1 on any A2 _{fl} or A1 _{fl} substrate C _{fl} s1 on any derivative wood substrate
Residual indentation	ISO 24343-1 - EN 433			Required value: ≤ 0.20 mm Average measured value: 0.08 mm Best measured value*: 0.07 mm
Castor wheel test	ISO 4918 - EN 425			No damage
Furniture leg	EN 424			No damage
Curl resultant to heat	ISO 23999 - EN 434			≤ 8 mm
Electrostatic properties	EN 1815 / EN 1081			< 2 kV on concrete / R ₁ > 10 ⁹ Ω
Hygiene				Does not contribute to infection spreading
Chemical resistance	ISO 26987 - EN 423			High resistance
Thermal resistance	EN 10456			0.04 m² K/W
Underfloor heating				Suitable
Light fastness	EN ISO 105-B02			≥ 6
Slip resistance	DIN 51130 / EN 13893			R9 / μ ≥ 0.3
Colours		12	9	Spaghetti XXL: 2 - Spaghetti: 8 Spice & Candy: 18, Havane: 5 - Uni: 4, Pastille: 2 - Draft: 6

HETEROGENEOUS
COMPACT VINYLAccent
Evolution

Specification

Compact flexible vinyl floorcovering. This HE vinyl is reinforced with TopClean XP™ and built-in fungistatic and bacteriostatic treatment.

Product standard: ISO 10582.




CERTIFICATION & CLASSIFICATION	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Type of floorcovering	ISO 10582			Heterogeneous compact vinyl
UPEC Classification	EN ISO 717-2			Type I
Classification	ISO 10874 - EN 685			U4P3E2/3C2
				34-43
TECHNICAL CHARACTERISTICS	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Wear layer thickness	ISO 24340 - EN 430	1.00 mm	0.90 mm	0.90 mm
Surface Treatment		TopClean XP™	TopClean XP™	TopClean XP™
Total thickness	ISO 24346 - EN 428	2.10 mm	2.00 mm	2.00 mm
Total weight / m²	ISO 23997 - EN 430	3100	2990	2990
Form of delivery	ISO 24344 - EN 426 Sheet (rolls)			approx. 23 running metres x 200 cm
TECHNICAL PERFORMANCES	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Dimensional stability	ISO 23999 - EN 434			Length + width < 0.10%
Reaction to fire	EN 13501-1			B _{fl} s1 on any A2 _{fl} or A1 _{fl} substrate B _{fl} s1 on any derivative wood substrate
Residual indentation	ISO 24343-1 - EN 433			Required value: ≤ 0.10 mm Average measured value: 0.05 mm
Castor wheel test	ISO 4918 - EN 425			No damage
Furniture leg	EN 424			No damage
Curl resultant to heat	ISO 23999 - EN 434			≤ 8 mm
Electrostatic properties	EN 1815 / EN 1081			< 2 kV on concrete / R ₁ > 10 ⁹ Ω
Hygiene				Does not contribute to infection spreading
Chemical resistance	ISO 26987 - EN 423			High resistance
Thermal resistance	EN 10456			0.02 m² K/W
Underfloor heating				Suitable
Light fastness	EN ISO 105-B02			≥ 6
Slip resistance	DIN 51130 / EN 13893			R9 / μ ≥ 0.3
Colours		12	9	Spaghetti XXL: 2 - Spaghetti: 8 Spice & Candy: 18, Havane: 5 - Uni: 4, Pastille: 2 - Draft: 6

The above information is subject to modification for the benefit of further improvement (05/14).

*For information - not binding

For more detailed technical information, please contact Tarkett. Please follow Tarkett's installation and maintenance instructions, included on the packaging, carefully.

CUSTOMS TARIFF : 482050000000F



■ **WESTERN EUROPE:** Austria: Tarkett Holding GmbH, Niederlassung Wien – Tel. +43 1 47 88 062 ■ **Belgium:** Tarkett France Belux – Tel. +32 16 35 98 80 ■ **Denmark:** Tarkett A/S – Tel. +45 43 90 60 11 ■ **Finland:** Tarkett Oy – Tel. +358 9 4257 9000 ■ **France:** Tarkett SAS – Tel. +33 1 41 20 42 49 ■ **Germany:** Tarkett Holding GmbH, Bereich Objekt – Tel. +49 62 33 810 ■ **Greece:** Tarkett Monoprosopi Ltd – Tel. +30 210 6745 340 ■ **Italy:** Tarkett S.p.A. – Tel. +39 0744 7551 ■ **Luxembourg:** Tarkett GD SA – Tel. +352 949 211 8804 ■ **Netherlands:** Tarkett Holding GmbH, Vestiging Nederland – Tel. +31 416 68 54 91 ■ **Norway:** Tarkett AS – Tel. +47 32 20 92 00 ■ **Portugal:** Tarkett SA – Tel. +351 21 427 64 20 ■ **Spain:** Tarkett Floors S.L – Tel. +34 91 358 00 35 ■ **Sweden:** Tarkett Sverige AB – Tel. +46 771 25 19 00 ■ **Switzerland:** Tarkett Holding GmbH, Bereich Objekt Schweiz – Tel. +41 043 233 79 24 ■ **Turkey:** Tarkett Aspen – Tel. +90 212 213 65 80 ■ **United Kingdom:** Tarkett Ltd – Tel. +44 (0) 1622 854 040 ■ **EASTERN EUROPE:** Baltic Countries: Tarkett Baltics: Tel. +370 37 262 220 ■ **Czech Republic:** Tarkett France SAS, org. slozka – Tel. +420-271 001 602 ■ **Hungary:** Tarkett France SAS – Tel. +36 1 437 8150 ■ **Poland:** Tarkett Polska Sp. z o. o. – Tel. +48 22 639 31 68 ■ **Russian Federation:** ZAO Tarkett RUS – Tel. +7 495 775 3737 ■ **Slovakia:** Tarkett France SAS, org. slozka – Tel. +421 248 291 317 ■ **South East Europe:** Tarkett Trade d.o.o. – Tel. +381 21 7557 649 (44) 569 12 21 ■ **Ukraine:** Tarkett UA – Tel. +38 (0) 44 569 12 21 ■ **ASIA AND OCEANIA:** Australia: Tarkett Australia Pty Ltd – Tel. +61 2 88 53 12 00 ■ **China:** Tarkett Floor Covering (Shanghai) Co. Ltd. – Tel. +86 (21) 60 95 68 38 ext 841 ■ **North East Asia:** Tarkett Hong Kong Limited – Tel. +852 2511 8716 ■ **India:** Tarkett France (India Branch) – Tel. +91 11 4352 4073 ■ **South East Asia:** Tarkett Flooring Singapore Pte. Ltd. – Tel. +65 6346 1585 ■ **AFRICA:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **MIDDLE EAST:** Tarkett Middle East: Tel. +961 1 51 3363/4 ■ **Israel:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **NORTH AMERICA:** USA: Tarkett Inc. – Tel. +1 713 869 5811 / Johnsonite – Tel. +1 440 543 8916 ■ **Canada:** Tarkett Inc. – Tel. +1 450 293 173 ■ **LATIN AMERICA:** Brazil: Tarkett – Tel. 55 12 3954 7108 ■ **Argentina - Chile - Uruguay:** Tarkett Latam Mercosur – Tel. 54 91 47 08 07 72 / 54 91 44 46 88 82 ■ **Colombia - Panama - Bolivia - Ecuador - Paraguay - Peru - Trinidad and Tobago:** Tarkett – Tel. 55 11 9 8410 9310 ■ **Mexico / Central America:** Tarkett Latam Mexico – Tel. 52 735 392-3948



www.professionals.tarkett.com