



Housing

HETEROGENEOUS
ACOUSTIC VINYL
Nordic
Stabil



THE ULTIMATE
FLOORING EXPERIENCE

Nordic Stabil

Nordic Stabil, Product standard EN 653

Heterogeneous vinyl floor covering, glass fiber reinforced. PVC foam backing with polyester to be glued down or loose laid on dry substrates. Suitable for housing or public spaces with low traffic. TopClean polyurethane reinforcement. In sheet form.

TECHNICAL CHARACTERISTICS		
Classification	ISO 10874 - EN 685	23/31
Total thickness	ISO 24346 - EN 428	2,80 mm
Wear layer thickness	ISO 24340 - EN 429	0,35 mm
Total weight	ISO 23997 - EN 430	1860 g/m ²
PUR treatment		TopClean XP
Abrasion Group	EN 660-2	Group T : ≤ 2.0 mm ³
Residual indentation	ISO 24343-1 - EN 433	0,25 mm
Dimensional stability	ISO 23999 - EN 434	< 0,10 %
Reaction to fire	EN 13501-1	Cfl s1
Electrostatic properties	EN 1815	< 2 kV on concrete
Impact sound reduction	EN ISO 717-2	18 dB
Acoustical improvement	NF S 31-074	16 dB
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	ISO 26987 - EN 423	Good resistance
Thermal resistance Underfloor heating	EN ISO 10456	0,05 m ² K/W Approved for max. 27° C
Form of delivery	ISO 24344 - EN 426 Sheet (rolls)	ca. 35 x 2 m
Colours		20

The above information is subject to modification for the benefit of further improvement (04/2015)

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please visit our websites or contact your local sales man for the instructions. Minor variations in color and pattern from samples may occur. When using a loose-lay solution, a floor protection must be used under castor chairs.

ARTICLE	PATTERN SIZE	DROP MATCH	LAYING	NCS	WELDING ROD
3532026	6,6 x various	*	↑↑	S2005-Y40R	1287069
3532044	6,6 x 33,3	*	↑↑	S4030-Y30R	1291451
3532027	10 x 100	*	↑↑	S6010-Y50R	1287492
3532028	10 x 100	*	↑↑	S3020-Y30R	1287153
3532029	11 x 100	*	↑↑	S3030-Y20R	1287153
3532030	11 x 100	*	↑↑	S5005-Y20R	1287497
3532031	11 x 100	*	↑↑	S3010-Y20R	1292762
3532022	16 x 16	33	↑↑	S8000-N/S1002-Y50R	1287314
3532032	-	100	↑↑	S6005-Y80R	1287333
3532033	-	100	↑↑	S2005-Y30R	1287427
3532034	25 x 25	50	↑↑	S2005-Y40R	1287069
3532035	25 x 25	50	↑↑	S6005-Y80R	1287333
3532036	25 x 50	50	↑↑	S2005-Y40R	1287069
3532037	25 x 50	50	↑↑	S2002-Y	1292455
3532038	-	0	↑↓	S2005-Y40R	1291821
3532039	-	0	↑↓	S1505-Y30R	1287069
3532040	-	0	↑↓	S6005-Y50R	1287546
3532041	-	0	↑↓	S6005-Y80R	1287333
3532042	-	0	↑↓	S3005-Y50R	1287530
3532043	-	0	↑↓	S2005-Y50R	1287290

*100 cm for an exact registration. A shift in the pattern transverse joints by 20 cm is often enough for a good pattern image.



BSAB MFK.1
EN 653, 23/31
2009-04-01



Information

SUOMI/FINLAND Tarkett Oy

Lars Sonckin kaari 16, 02600 Espoo
Puh : (09) 4257 9000 - Fax : (09) 4257 9090
info.fi@tarkett.com
www.tarkett.fi

NORGE Tarkett AS

Postboks 500, Brakerøya, 3002 Drammen
Tel : 32 20 92 00 - Fax : 32 20 92 01
info.norway@tarkett.com
www.tarkett.no

SVERIGE Tarkett AB

Box 4538, 191 24 Sollentuna
Tel : 0771-25 19 00 - Fax : 08-96 62 83
info.se@tarkett.com
www.tarkett.se



www.tarkett.com