CLASSICAL LIVING

Technical data sheet

TARKETT Extreme Protection | TARKETT MAT Effect | GUARANTEE 15 years Residential use | Anti-slip | Easy to clean | FAST!

2.4mm thick with 0.35mm wear layer
Extra resistant to scuffs, scratches and stains
Easy to install and maintain
15-year warranty

CE EN 14041:2004
No. 0004-0023-DoP-2015-01
www.home.tarkett.co.uk
Manufactured by: Tarkett Holding GmbH - 122, Granastrasse 54329 Konz, Germany

Vinyl floor Covering	EN ISO 26986		
Classes of Use	EN ISO 10874	23	32

PRODUCT ID

Total Thickness	EN ISO 24346	2,40 mm
Wear Layer Thickness	EN ISO 24340	0,35 mm
Weight	EN ISO 23997	1,730 kg/m²
Roll Width	EN ISO 24341	4+3+2m
Roll Length		25 m
Impact Sound Absorption	EN ISO 717-2	16 dB
Residual Indentation	EN ISO 24343-1	≤ 0,20 mm
Castor Chair	ISO 4918	OK
Wear Layer Binder content	ISO 11638	Type I

PRODUCT SAFETY & SECURITY CHARACTERISTICS

Slip Resistance	EN 13893 DIN 51130	μ ≥ 0,30 R10
Static Electrical Propensity	EN 1815	≤ 2 kV
Fire Classification	EN 13501-1	Cfl-S1
Chemical Resistance	EN ISO 26987	Not Affected*

PRODUCT ENVIRONMENTAL BEHAVIOR

Dimentional Stability	EN ISO 23999	≤ 0,40 %
Thermal resistance for underfloor heating	ISO 10456 EN 12524-1	0,06 m²/kW
Light Fastness	EN ISO 105 B02	≥ 6

PHTHALATE FREE Technology* — *Except recycled content

<100μg/m³* Better Indoor Air Quality — *TVOC AT 28 DAYS

100 % Recyclable

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+ (A+ A B C)

*For short-term exposure of dilute acids, oils and fats, no change in the material properties.

Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.

Tarkett