

HETEROGENEOUS
VINYL
FLOORCOVERING

CONTRACT WOOD & CONTRACT NATURE



2DAY
express
Core collection from Tarkett
AVAILABLE TODAY FROM STOCK



Tarkett's commitments to VOC* emissions

Volatile organic compounds (VOCs) are emitted as gases from manmade materials such as flooring as well as natural ones like trees. To improve indoor air quality, Tarkett has invested significantly in the research of raw materials and flooring manufacturing processes to reach near zero emission levels. Since September 2011 all Tarkett's homogeneous vinyl flooring has emissions below quantifiable level - measuring less than 10 µg/m³ TVOC after 28 days*. All other commercial floorings that Tarkett manufactures currently release less than 10 µg/m³ TVOC after 28 days - ten times lower than European standards. We'll continue to focus on safer, healthier solutions to reduce emission levels across all products, for improved indoor air quality and a healthier quality of life.
* ISO standards 16000-3/-6/-9/-11

						
Contract Wood	Contract Nature	*TVOC AT 28 DAYS	www.profiles.tarkett.com	Heterogeneous to EN 649 have a generic A+ environmental rating in major use areas such as healthcare, education and retail. www.bre.co.uk/greenguide	PUR REINFORCED	
					According to European Classification ISO 10874 EN 685	
Contract Wood 0131-0037-DuP-2013-07 http://professionals.tarkett.com Manufactured by: Tarkett Luxembourg SA L-9779 Luxembourg - Luxembourg		Contract Nature 0131-0056-DuP-2014-17 http://professionals.tarkett.com Manufactured by: Tarkett Luxembourg SA L-9779 Luxembourg - Luxembourg				
						

Classification	Standards	Contract Wood & Contract Nature	Contract Nature Acoustic
Type of floorcovering	ISO 10582 Type I EN 651	Resilient floorcovering - Heterogeneous compact poly (vinyl chloride) floorcovering	Resilient floorcovering Polyvinyl chloride floorcovering with foam layer
Classification	ISO 10874	Commercial 34 Industrial 43	Commercial 34 Industrial 42

Technical Characteristics	Standards	Contract Wood & Contract Nature	Contract Nature Acoustic
Total thickness	ISO 24346	2.00mm	3.00mm
Total wear layer thickness	ISO 24340	0.70mm	0.70mm
Total weight / m ²	ISO 23997	3000 g/m ²	2500 g/m ²
Polyurethane reinforcement	-	TOP CLEAN	TOP CLEAN
Wear layer binder content	ISO 10582	Type I	Type I
Form of delivery	ISO 24341 Sheet (rolls)	Approx. 23 running metres x 200cm 2m Compact 25098 ___ 4m Compact 25099 ___ (3 digit colour no.)	Approx. 23 running metres x 200cm 2m Acoustic 25086 ___ (3 digit colour no.)

Technical Performances	Standards	Contract Wood & Contract Nature	Contract Nature Acoustic
Impact sound reduction	EN ISO 717/2 NF S31-074	Δ Lw = 5 dB Class C	Δ Lw = 19 dB Class A
Residual indentation	Av. measured value ISO 24343-1	0.02mm ≤ 0.10 mm	0.11mm ≤ 0.20 mm
Reaction to fire	EN 13501-1	Bfl s1 glued over concrete and wood substrates	Cfl s1 glued over concrete and wood substrates
Slip resistance	DIN 51130 EN 13893	R10 ≥ 0.30	R9 ≥ 0.30
Dimensional stability	ISO 23999	≤ 0.10%	≤ 0.10%
Furniture leg	EN 424	No damage	No damage
Castor chair test	ISO 4918	No damage	No damage
Curl resistant to heat	ISO 23999	≤ 8 mm	≤ 8 mm
Total VOC emissions	ISO 16000	< 100µg/m ³	< 100µg/m ³
Light fastness	ISO 105-B02	≥ 6	≥ 6
Chemical resistance	ISO 26987	High Resistance	High Resistance
Electrostatic property	EN 1815 EN 1081	< 2kV on concrete R1 > 10 ⁹ ohms	< 2kV on concrete R1 > 10 ⁹ ohms
Thermal resistance Underfloor heating	EN ISO 10456	0.02m ² K/W Suitable	0.04m ² K/W Suitable
Colours		13 wood / 9 nature	7

The above information is subject to modifications for the benefit of further improvement. (02/17)

For more detailed technical information please contact Tarkett. Follow Tarkett's installation and maintenance instruction carefully, available on request. The values shown in the technical data are "typical values" and there may be some statistical variation away from the value shown. E&OE

INSTALLATION NOTICE. Not suitable for double drop installation.
Contract Wood & Contract Nature products are supplied with a special back coating film making them unsuitable for double drop installation.
Please refer to installation instructions for full details.

Tarkett Limited Lenham, Maidstone, Kent ME17 2QX, United Kingdom. Tel 01622 854040 Fax 01622 854520 www.tarkett.co.uk Email: uksales@tarkett.com



www.tarkett.co.uk

Contract Wood & Contract Nature 02/2017