

PROFESSIONAL

WOOD Product Datasheet 2016



TECHNICAL DATA (EN 13489)		10 mm	13 mm	14 mm	22 mm
Reaction to fire	EN 13501-1	Dfl-s1			
Emission of formaldehyde	EN 13986	E1			
Brinell hardness (average value)	(BHN) EN1534				
Oak		3,7			
Ash		4,0			
Taber Abraser/Lacquer's wear resistance	EN 13696				
Protoco Lacquer		4000			
Protoco Natura		3500			
<i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>					
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17			
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,079 0,099 0,119	0,101 0,121 0,141	0,152 0,182 0,192	
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,102	0,104	0,11	0,136

INSTALLATION	
Installation method 10 - 14 mm 22 mm	Floating or glue down Floating, nailed or glue down
Installation instruction	Download from tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

SIZE AND PACKAGE	10x162x1245	13x194x2027
Thickness (mm)	10	13
Width (mm)	162	194
Length (mm)	1245	2027
Wear layer thickness (mm)	2,5	2,5
Boards/pack	8	6
m ² /pack	1,61	2,36
m ² /pallet	77,28	94,40
Weight/m ² (kg)	5,4	7,3

SIZE AND PACKAGE	14x194x2027	22x194x2535
Thickness (mm)	14	22
Width (mm)	194	194
Length (mm)	2027	2535
Wear layer thickness (mm)	3,5	3,5
Boards/pack	6	4
m ² /pack	2,36	1,97
m ² /pallet	94,40	68,95
Weight/m ² (kg)	7,9	10,6

Due to the nature of the material this table shows typical values.

MAINTENANCE
Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Professional 10-14 mm
Protoco Lacquer / Protoco Natura

TARKETT SUSTAINABILITY TAG	98 % 98 %	100 %
	Natural Renewable	Recyclable

Professional 22 mm
Protoco Lacquer

TARKETT SUSTAINABILITY TAG	99 % 99 %	100 %
	Natural Renewable	Recyclable



PROFESSIONAL

DESIGN

Real wooden floors for special applications

PRODUCT DATA	Material code	Size (mm)			Pattern	Surface treatment	Surface effect	Bevel (2 side)	Stained	DoP no.
		Thickness	Width	Length						
PROFESSIONAL 10 MM										
Oak Cotton White brushed	8725003	10	162	1 245	1-strip	Proteco Natura	Brushed	Minibevel	Yes	0190-0002
Oak Sandy Grey brushed	8725004	10	162	1 245	1-strip	Proteco Natura	Brushed	Minibevel	Yes	0190-0002
Oak Nature brushed	8725006	10	162	1 245	1-strip	Proteco Natura	Brushed	Minibevel	No	0190-0002
Oak Country brushed	8725002	10	162	1 245	1-strip	Proteco Natura	Brushed	Minibevel	No	0190-0002
Oak Country Praline brushed	8725005	10	162	1 245	1-strip	Proteco Natura	Brushed	Minibevel	Yes	0190-0002
PROFESSIONAL 13 MM										
Oak Nature	8722001	13	194	2 027	3-strip	Proteco Lacquer	-	-	No	0020-0104
	8722002	13	194	2 027	3-strip	Proteco Natura	-	-	No	0020-0104
PROFESSIONAL 14 MM										
Oak Nature	8721001	14	194	2 027	3-strip	Proteco Lacquer	-	-	No	0020-0106
	8721002	14	194	2 027	3-strip	Proteco Natura	-	-	No	0020-0106
PROFESSIONAL 22 MM										
Ash Nature	7949007	22	194	2 535	3-strip	Proteco Lacquer	-	-	No	0020-0017
Oak Nature	7825011	22	194	2 535	3-strip	Proteco Lacquer	-	-	No	0020-0017

PROFESSIONAL 10 MM



Oak Cotton White brushed



Oak Sandy Grey brushed



Oak Nature brushed



Oak Country brushed



Oak Country Praline brushed

PROFESSIONAL 13/14 MM



Oak Nature

PROFESSIONAL 22 MM



Ash Nature



Oak Nature

The pictures only present the color of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com
Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.

For further and latest information please visit www.tarkett.com