ACOUSTIC HETEROGENEOUS VINYL STAIR SYSTEM WITH TOPCLEAN XP

Tapiflex Stairs

Cleaning instructions

Modern day-room cleaning aims to reduce wet cleaning procedures and replace them with drier cleaning techniques. For example, the use of centrally laundered pre-impregnated mops and the wide application of appropriate machines. This makes work more effective and easier for the cleaning staff, and minimises environmental impact. Less cleaning chemicals and less fresh water are used

Jan 2011

General advice

- Clean the floorcovering regularly, as this is more cost-effective and hygienic than occasional heavyduty cleaning.
- Always follow dosage instructions carefully.
- Wipe up any grease and spilt oil immediately, as they may damage the surface.
- Resilient floors are damaged by solvents.
- Remember that light colours need more frequent cleaning.

Preventive care



Entrance matting

About 80% of surface soiling that has to be cleaned off is brought in from outside. And 90% of that soiling can be avoided using an effective and correctly dimensioned

The less dirt that comes in through the entrance, the lower the maintenance requirements.

Daily and regular cleaning



Damp mopping

Use a mop dampened with water or detergent solution. It is essential that water does not stay on the floor or leave a film. The floor should be virtually dry after 15-20 seconds.



Spot and stain removal

Treat stains immediately.

Spot clean by hand with a white/red nylon pad and neutral detergent (solvents should not

Work from the outside of the mark towards its centre. Rinse and wipe afterwards with clean water.

Periodic cleaning



Manual brush

Clean the stairs manually using a medium brush and diluted floor cleaner (pH 7-10).





TopClean XP surface treatment

The TopClean X-treme Performance surface treatment is based on a photoreticulated PUR coating reinforced with alumina oxide. It ensures very good resistance to abrasion and very easy, low-cost maintenance – no wax, no polish, for life!

Initial site cleaning

Always protect the stairs during the construction period. After installation, always clean the new floor: vacuum, sweep or damp mop the area to remove building dust and loose

If you have any questions, please contact your local Tarkett representative for further information. The above information is subject to change due to continuous improvement.

