

# MAINTENANCE INSTRUCTIONS

## Linoleum Sicuro

2013

To help protect your floorcovering from varying levels of traffic and also as the first defence against the weather, we strongly recommend that barrier mats be installed at entry points to the building to limit the amount of wet and dry soiling. If maintained correctly, these barrier mats should limit the transfer of foot borne contamination and make the daily cleaning and maintenance programme even easier.

Polish or maintainers should never be applied to Linoleum Sicuro, as this would reduce the effectiveness of the surface profile and slip resistance. The unique PUR factory applied surface treatment assists with the ease of maintenance.

### **Initial Treatment**

1. Allow at least 2 days from the completion of the installation of the floorcovering, prior to carrying out any wet cleaning.
2. Ensure that all trace of adhesive is removed from the surface of the floorcovering.
3. Sweep floor area with a soft broom to remove any debris.
4. Depending on the level of site soiling after the installation is complete, it may be necessary to scrub the floor clean, prior to adopting the daily maintenance regime. Please find the following options.
  - a) Mop clean using SYR Scrubclean system with Scrubclean Solution neutral PH detergent \*.
  - b) Scrub the surface of the Linoleum Sicuro using a contra rotating cylindrical machine, rotary scrubber or a scrubber-dryer standard speed machine fitted with a medium brush.
  - c) Rinse area clean with hot water (if required).

### **Routine Maintenance**

#### **Non-Mechanical Method**



1. Sweep floor area with a soft broom to remove any debris.
2. Mop clean using SYR Scrubclean system with Scrubclean Solution neutral PH detergent \*. (SYR CS3 \*, should be carefully used on areas that are heavily soiled or greasy)
3. Rinse area clean with hot water and allow to dry completely (if required).

#### **Mechanical Method**



1. Sweep floor area with soft broom to remove any debris.
2. Spray apply a solution of SYR CS1 \*, diluted as per the manufactures recommendation. A pump-up spray will allow for even distribution and economy of the cleaning solution (SYR CS3 \*, should be carefully used on areas that are heavily soiled or are greasy. Leave to stand for 5-10 minutes).
3. Scrub the surface of the Linoleum Sicuro using a contra rotating cylindrical machine, rotary scrubber or a scrubber-dryer standard speed machine fitted with a medium brush.
4. Rinse area clean with hot water and allow to dry completely (if required).

(\* See the attached details below).



# Part of the SCRUBCLEAN<sup>®</sup> RANGE

## The ULTIMATE<sup>®</sup> System



### Recommended by Tarkett for floor cleaning

Launders mopheads during work procedures in 35 seconds.

Cleans floors and other surfaces as often as required with a Wipe or Mophead that is laundered cleanly every time.

Cuts traditional detergent use by 60%

Water inside bucket is cleaned during work progress so that water usage is cut by 70%

DRY, SAFE FLOORS

Many other features can be shown during a demonstration which would illustrate the unique advantage associated with the ULTIMATE System

### Tarkett also recommends

SYR's Scrubclean solution working in harmony with the SYR Ultimate scrubclean system for general purpose cleaning.

For general purpose cleaning with other mopping systems use SYR's CS1 Filtakleen chemical.

For greasy or heavily soiled areas use SYR's CS3 Scrunge chemical.



[www.syrclean.com/scrubcleanrange](http://www.syrclean.com/scrubcleanrange)

Email: [safefloors@syrclean.com](mailto:safefloors@syrclean.com) Telephone: 01384 421215